


Line Notify Module IKA series



IKa-001



IKa-RS232



**Easy
Wiring**

**Quick
Configuration**

**Data capture
on web**



Line Notify Module IKA series

Introducing InKnow Alert's new, Notify module alert & logger
with inknow smart technology !

InKnow Alert's new IKA-001 (for 8 channel) and IKA-RS232 send message via LINE notify and capture data on web service. Two types of notify modules provide alert via LINE application and recording capabilities for Fire alarm , water leak , machine error...etc, data is logged using a high-speed recording across all channels every 1 minute. InKnow Smart technology makes it possible.



8-Channel (Dry Contact)



RS-232

(*Available with FCP)



InKnow Smart Data Transmission !

InKnow Alert enable Web Service Data Transmission

**Quick
Configuration**

**Real-Time saved
on Web Service**



Data is sent to web service for recorder max 3 month
facilitating report at even and location from everywhere on PC
and can download data to excel file.

A screenshot of a web application interface. It features a sidebar on the left with navigation links like 'Home', 'Alerts', 'Data', 'Reports', and 'Settings'. The main area displays a table with columns for 'ID', 'Name', 'Status', 'Location', 'Alert Type', and 'Last Update'. The table contains several rows of data, including entries for 'InKnow Smart' and 'InKnow Alert'.

Notify Module IKA-001



Small and light enough for the palm of your hand



Key Feature

Eight Digital Input Channels

Ultra-compact for convenient installation

Alert via Group LINE to 500 members


Fast Alert within 1 minute and Recording Across All Channels



LAN connection



8-Channel




Logger data on InKnow Smart system
Max 3 Month

Key Feature Upload Layout



Fire Alarm Here !!!

For Application such as ; Fire Alarm , Gas Detector , Motor , Temperature&Humidity Machine , Water&Chemical Tank , Pump



Notify Module IKA-RS232



Innovation & Easy operation , Available with Fire Alarm Control Panel

Key Feature

RS232 Signal , RX-TX-GND

Ultra-compact for convenient installation

Available with Fire Alarm Control Panel


Alert & Detect Trouble Shooting via Group LINE to 500 members



LAN connection



RS232- 3 bit terminal block



Logger data on InKnow Smart system
Max 3 Month



Key Feature

Detect Trouble Shooting's FCPA
convenient for Maintenance system



Available with Fire Alarm Control Panel



Model	IKA-001	IKA-RS232
Alert Message	LINE Notify - TH/EN	LINE Notify - EN Only
Mechanical Specification		
Dimension	Height: 950 mm Width: 105 mm Depth: 250 mm	Height: 950 mm Width: 105 mm Depth: 250 mm
Electrical Specification		
External power supply voltage	24VDC	24VDC
Ethernet Speed	10/100 Mbps	10/100 Mbps
LED Status	RED's "ON" GREEN's "Online"	RED's "ON" GREEN's "Online"
Configuration	InKnow Smart Web service	InKnow Smart Web service
Interface type:	Dry contact 8 terminal block (female)	RS-232 side 3 bit terminal block
Transmission:	15M	15M
Signal	I/O	TXD,RXD,GND
Parity bit:	-	None, Even, Odd, Mark
Data bit:	-	7bit,8bit
Baud rate:	-	600bps~115200bps
Stop bit	-	1,2
Environmental Specifications		
Temperature Range	0°C to +55°C	0°C to +55°C
Humidity Range	5% to 95% relative humidity	5% to 95% relative humidity



Distribute By

PM Solution Control Co., Ltd.

Head Office

14/4 Moo.6 Bang-korbua Subdistrict
Phapadeang District Samutprakarn
Zipcode 10130 Thailand
TEL : (+66) 095-940-4147
E-mail : sale.pm2@gmail.com
<http://www.pm-io.com>

